

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



✓ (43) International Publication Date
3 June 2004 (03.06.2004)

PCT

(10) International Publication Number
WO 2004/047258 A2

(51) International Patent Classification⁷: **H02K 21/00**

(72) Inventor; and

(21) International Application Number:
PCT/JP2003/014667

(75) Inventor/Applicant (for US only): **TAKEUCHI, Ke-
satoshi** [JP/JP]; c/o **SEIKO EPSON CORPORATION**,
3-5, Owa 3-chome, Suwa-shi, Nagano 392-8502 (JP).

(22) International Filing Date:
18 November 2003 (18.11.2003)

(74) Agents: **INABA, Yoshiyuki et al.**; **TMI ASSOCIATES**,
23rd Floor, Roppongi Hills Mori Tower, 6-10-1, Roppongi,
Minato-ku, Tokyo 106-6123 (JP).

(25) Filing Language: English

(81) Designated States (national): **CN, JP, KR, US.**

(26) Publication Language: English

(84) Designated States (regional): European patent (AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,
IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(30) Priority Data:
2002-334160 18 November 2002 (18.11.2002) JP
2003-157229 2 June 2003 (02.06.2003) JP
2003-175456 19 June 2003 (19.06.2003) JP
2003-313170 4 September 2003 (04.09.2003) JP


Published:

— without international search report and to be republished
upon receipt of that report

(71) Applicant (for all designated States except US): **SEIKO
EPSON CORPORATION** [JP/JP]; 4-1, Nishishinjuku
2-chome, Shinjuku-ku, Tokyo 163-0811 (JP).

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: **MAGNETIC STRUCTURE AND MOTOR EMPLOYING SAID MAGNETIC STRUCTURE, AND DRIVER COM-
PRISING SAID MOTOR**



(57) Abstract: Provided is a small motor su-
perior in weight/torque balance. A phase sta-
tor 10 and B phase stator 12 are disposed to
face each other. A rotor is interpositioned
between these stators. Electromagnetic coils
18 are provided to the stators evenly in the cir-
cumferential direction. A permanent magnet
is provided to the rotor evenly in the circum-
ferential direction. The exciting polarity of
the electromagnetic coil is alternately oppo-
site, and this is the same for the permanent
magnet. A signal having a prescribed fre-
quency is input to the A phase electromag-
netic coil and B phase electromagnetic coil.
The rotor rotates between the stators as a re-
sult thereof.

WO 2004/047258 A2